



**STANDARD SPECIFICATIONS:** Door body .063" tempered aluminum alloy, satin anodized finish. 9" x 14" clear acrylic safety window set in black rubber molding. Door assembly includes Save-T hinges and both 1/4" - 20 x 1" thread cutting screws and #14 -1-1/2" sheet metal/wood screws for jamb by others. **OPTIONAL:** 16-Gauge Stainless Steel door body.

**INSTALLATION DETAILS:** Jamb must be plumb and square. Minimum double 2 x 4 inch wood construction or equivalent. Hollow metal jamb should be reinforced at hinge locations.

### SPECIFIC DETAILS FOR DOOR CONSTRUCTION:

**DOOR CONSTRUCTION:**

.063" Aluminum      16-gauge stainless steel      0.63" Aluminum with Laminate: \_\_\_\_\_

**WINDOW:**

Standard 9" X 14" In Black Rubber Molding, Up 60" to Center of Window from Floor  
 Other: \_\_\_\_\_

**LOWER HINGE:**

Bottom Pin is Standard

**KICK PLATE:**

Black                      Same Color                      Stainless Steel                      Other \_\_\_\_\_                      Height: \_\_\_\_\_

**NOTES:**

_____ Company Name	_____ Purchase Order #	_____ Curtron Order#
X _____ Signature (Required)	_____ Print Name	_____ Date

*Charges will be assumed by buyer for changes or cancellations to work in process. Buyer hereby accepts responsibility for all sizes and dimensions. This order will not be processed until all acknowledgment forms are signed and returned.*