

Model:  
KBM2F

**Traditional Reach-In's:**  
*Reach-In Solid Swing Door Freezer*



**KBM2F**

- **Stainless steel interior and exterior** retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**  
Heavy-duty pull handle  
Each door with two spring hinges, this make the door self-closing with with enduring quality
- **R290 Refrigeration system** holds -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- **Electronic control system:**  
Adjustable temperature set point and defrost frequency  
Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath


**Bottom mounted units feature:**

- "No stoop" lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

**Rough-In Data**

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
KBM2F	2	6	54 1371	32-1/4 818	82-1/2 2095	47 1321	1-	115/60/1	11.16	5-20P 

Plug type varies by country.



CONFORMS TO NSF/ANSI STD. 7

KINTERA EQUIPMENT, LLC

Add: PO BOX 1186, MANSFIELD MA 02048

Tel: 833-546-8372 Website: <https://kinteraequipment.com> E-mail: [info@kinteraequipment.com](mailto:info@kinteraequipment.com)

**KBM2F Plan View**

