Model: KBM3F	Traditional Reach-In's: *Reach-In Solid Swing Door Freezer*

KBM3F

- **Stainless steel interior and exterior** retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room
- **Standard door features:**
  Heavy-duty pull handle
  Each door with two spring hinges, this make the door self-closing with with enduring quality
- **R290 Refrigeration system** holds -8°F to 0°F (-22°C to -18°C) for the best in food preservation.
- **Electronic control system:**
  Adjustable temperature set point and defrost frequency
  Error codes to diagnose service issues
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath

Bottom mounted units feature:

- ”No stoop” lower shelf.
- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
KBM3F	3	9	80-7/8 2054	32-1/4 818	82-1/2 2095	72 2040	1	115/60/1	13.32	5-20P

Plug type varies by country.

CONFORMS TO NSF/ANSI STD. 7

KINTERA EQUIPMENT, LLC
Add: PO BOX 1186, MANSFIELD MA 02048
Tel: 833-546-8372 Website: https://kinteraequipment.com E-mail: info@kinteraequipment.com

KBM3F Plan View