

Model:
KTM2F

**Top Mount Series:
Reach-In Solid Swing Door Freezer**




KTM2F

- **CABINET CONSTRUCTION**
Stainless steel interior and exterior retains attractive finish longer.
- **Rounded corner** design inside of the cabinet makes it easy to clean the inside storage room.
- **LED Lights** with Proximity Door Switch Activates Inside Lighting.
- **Refrigeration system:**
High Performance, Balanced, Top-Mounted R290 Refrigeration system holds 0°F to -8°F (-18°C to -22°C) for the frozen foods and ice cream.
- **Insulation**-entire cabinet structure and solid door are foamed-in-place using a high density polyurethane insulation.
- **Electronic control system:**
Adjustable temperature set point and defrost frequency. Error codes to diagnose service issues.
- **Shelf:** Adjustable, heavy duty PVC coated shelves.
- **Standard heavy-duty casters** make it easy to move and clean underneath
- **Self-Closing Doors** With 120° Hold Open Feature.
- **Santoprene Door Gaskets**

Rough-In Data

Specifications subject to change without notice.

Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Model	Doors	Shelves	Cabinet Dimensions (inches) (mm)			CAP. CU.FT. LITER	HP	Voltage	Amps	NEMA Config.
			L	D	H					
KTM2F	2	6	54 1371	32-1/4 818	82-1/8 2086	47	3/4	115/60/1	7.1	5-15P 

Plug type varies by country.



CONFORMS TO NSF/ANSI STD. 7

KINTERA EQUIPMENT, LLC

Add: PO BOX 1186, MANSFIELD MA 02048

Tel: 833-546-8372 Website: <https://kinteraequipment.com> E-mail: info@kinteraequipment.com

