

Project:		
Model #:		
Item #:		
Available W/H:		Qty:
Approval:		
AIA #:	SIS #:	
CSI Section 11400		

## Sandwich / Salad Unit

Food Prep Tables **KINTERA** 

### Model : KS48



### \_\_\_\_ FEATURES & BENEFITS =\_\_\_

#### Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, KINTERA brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Cold air compartment

Our innovative "Cold Air Compartment" maintains temperature evenly for each pan to preserve fresh food longer. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

#### Cabinet construction

KINTERA model boasts a stainless steel exterior (door) with AL exterior sides (galvanized steel back and bottom). Interior is stainless steel floor and back with AL sides. It guarantees the utmost in cleanliness and long product life.

#### High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Convenient cutting board side rail
- Self-contained system
- 4" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included
- 9-1/2" deep, ½" thick cutting board included
- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 39°F for the best in food preservation

								NAT Refi	rigerant	intertek
Model	Product ID	Swing Doors	CU./FT.	#of Shelves	#of Pans	#of Hood	HP	AMPS	Crated Weight (Ibs.)	$L \ge D^* \ge H^{\dagger}$ (inches)
KS48	919705	2	16.26	2	12	1	1/3	3	269	481/4 x 30 x 371/2

Ver.20240514 Printed in U.S.A.

\* Depth does not include 1-1/4" for rear spacers. † Height does not include 4-3/4" for caster height.

# Sandwich / Salad Unit

### Model : KS48

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	<b>NEMA 5-15P</b>			
Full Load Amperes	3			
Compressor HP	1/3			
Cord Length (ft.)	9			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	16.26			
Ext. Length Overall (in.)	481/4 (1225mm)			
Ext. Depth Overall (in.)*	30 (764mm)			
Ext. Height Overall (in.)†	371/2 (952mm)			
# of Doors	2			
# of Shelves	2			
Shelf Size (L x D) (in.)	21 x 17			
Net Weight (lbs.)	249			
Gross Weight (lbs.)	269			


Design and specifications subject to change without notice. Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 1-1/4" for rear spacers. † Height does not include 4-3/4" for caster height.


# WARRANTY : 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

### **PLAN VIEW**

(unit : inch)



**TOP VIEW** 



SIDE VIEW

Ver.20240514

Intertek NATURAL Refrigerant 2 YEAR Compressor 5 YEAR WARRANTY Warranty: 800-381-7770 info@kinteraequipment.com

Continued product development may necessitate specification changes without notice.