

## Vacuum Packaging System Spec Sheet

<p><b>GREENVAC</b> VACUUM PACKAGING SYSTEM</p>	<p><b>FEATURES</b></p>
<p>ITEM: GV150-GN1/1</p>	<p>GN1/1 are manufactured with 17/18 gauge chrome nickel steel. In comparison, conventional containers are manufactured with 22/24 gauge steel. Oven safe.</p>
	<p><b>LIDS</b></p>
<p><b>DESCRIPTION</b></p>	<p>Developed from a high performance polyamide (Grilamid) Product Facts:</p> <ul style="list-style-type: none"> <li>•High impact resistance</li> <li>•High weather resistance</li> <li>•High chemical resistance</li> <li>•Perfect abrasions-resistance and sliding condition</li> <li>•Minimum water absorption very high dimensions stability</li> <li>•Minimum specific weight</li> <li>•Excellent high impact resistance</li> <li>•High barrier-character</li> <li>•Lids short term resistant to temperatures up to 194°F (dishwater)</li> </ul>
<p>The robust, stainless steel 1/1 GN vacuum packaging system is standard equipped with a vacuum lid, gasket seal &amp; nozzle. NSF certified.</p>	<p><b>SEALS</b></p>
<p><b>WARRANTY</b></p>	<p>The gaskets are made of food compatible silicone. The valve is produced from latex. All GreenVAC components are new developments for a use in high vacuum. The atmospheric pressure in such a vacuum has a value of 900 - 1700kg / cm<sup>2</sup> depending on the size of GreenVAC container!</p> <p>Used in connection with:</p> <ul style="list-style-type: none"> <li>•Henkelman Vacuum Machine w/External Adapter.</li> <li>•A retrofitted chamber machine.</li> <li>•Directly in the chamber of a standard vacuum machine, sizes are dependent on the chamber size.</li> </ul>
<p>All models shown come with Invacus standard one year warranty against defects in materials and workmanship. For full warranty details, please refer to: <a href="http://Invacus.com">Invacus.com</a></p>	
 	
<h1>GREEN VAC</h1>	
 <a href="http://www.invacus.com">www.invacus.com</a>	<p>Invacus LLC Sales and Technical Support 493 W Fullerton Ave Elmhurst IL, 60126</p> <p>Ph: +1 331 979 2013 E: <a href="mailto:info@henkelmanusa.com">info@henkelmanusa.com</a> Fax: +1 630 359 3875</p>

